



TWO DECKS SEMI DESPLACEMENT VESSEL	
SCHEDA TECNICA GAMMA 16	
<i>LOA</i>	18,20 m - 60 feet
<i>TYPE APPROVED LENGHT</i>	16,20 m - 53 feet
<i>LENGHT ON WATERLINE</i>	16,10 m - 52 feet
<i>MAXIMUM BEAM</i>	5,50 m - 18 feet
<i>DRAUGHT 1/2 LOAD</i>	1,35 m - 4,40 feet
<i>DISPLACEMENT 1/2 LOAD</i>	41 tons. - 90.390 lbs
<i>CLASSIFICATION</i>	CE A RINA
<i>HULL MATERIAL</i>	STEEL 42 , Grade A - STAINLESS STEEL AISI 316 L Quality
<i>DECK HOUSE STRUCTURE</i>	STEEL 42 , Grade A - STAINLESS STEEL AISI 316 L Quality
<i>FLYNG BRIDGE</i>	Alluminium Alloy AlMg 4,5 Mn H 321
<i>MAXIMUM SPEED</i>	13 Kn. (18 Kn. optional)
<i>CRUISING SPEED</i>	12 Kn (14 Kn. Optional)
<i>RANGE AT ECONOMIC SPEED</i>	1.210 Nm
<i>FUEL CONSUMPTION ECONOMIC SPEED</i>	30 lt/h
<i>FUEL TANK</i>	4.500 l - 990 gal.
<i>FRESH WATER</i>	1.500 l - 396 gal
<i>WASTE TANK</i>	600 l - 159 gal
<i>ENGINES</i>	VOLVO PENTA D6 330 - OPTIONAL: CATERPILAR ACERT C9 575 : CATERPILA ACERT C12 669
<i>ANTIDUMPING</i>	VETUS
<i>ELETTRICAL</i>	220 V Ac - 24/12 V Dc
<i>GENERATOR SETS</i>	1 X 17,5 Kw ONAN
<i>LAYOUT</i>	OWNER ROOM + BATHROOMS
	VIP + BATHROOM
	NR. 1 DOUBLE BEDROOMS
	1 CREW CABIN + BATHROOM

THE UPON RELATED DATAS MUST BE INTENDED AS APPROXIMATES ON THE BASIS OF THE CONSTRUCTION TECHNICAL DATAS